



# Toilet Paper Holder Replacement

Replace your toilet paper holder.

Written By: Elizabeth Opheim



## INTRODUCTION

Over time, the screws and brackets securing a toilet paper holder can loosen or become disconnected entirely. This guide will walk you through the steps of replacing a broken or loose toilet paper holder.



### TOOLS:

- [Tape Measurer](#) (1)
- [Screwdriver](#) (1)
- [Phillips #0 Screwdriver](#) (1)



### PARTS:


- [Safety Glasses](#) (1)
- [Marker](#) (1)




## Step 1 — Toilet Paper Holder




- Unscrew the four screws of the original broken holder.

 You may want to wear gloves.

 If there is damage to the wall behind the old holder, check out the iFixit guide for [repairing a hole in drywall](#).

## Step 2



- Measuring the area where you want your new holder to go, mark two lines 6.8" apart.
  - Measure an inch and a third (1 and 1/3") above the marks and mark these new spots where your screws will go.
-  While marking where you want to place the new holder, use a leveling tool to make sure that the toilet paper will be sitting flat.

### Step 3



- Place the new screw inside the new bracket and line up the mark with the base of the screw.
  - ☑ Make sure that the indentation for the toilet paper holder is facing in.
- Repeat this for the top and bottom screws on both the left and right bracket bases (4 times total).

### Step 4



- Insert the spring loaded toilet roll bar and enjoy.

Hopefully you have enjoyed exploring this repair guide and now understand how to repair and replace a broken toilet paper roll holder.

This document was last generated on 2017-10-08 02:56:48 AM.